



### REMACHE POP ABIERTO DURALUMINIO - ACERO

Código	Diámetro "D" mm (pulg)	Largo "L" mm	Envase	Diám "D1"	Altura "A"	Rango de Agarre, mm	Diámetro Broca, mm	Resistencia, kg Tracción/Cizalle	Remachadora apropiada
AD32BS	2.4 (3/32")	5.7	100 U	4.7	0.9	0.8 - 3.1	2.5	79 / 56	PWL30 PRG510
AD34BS		8.9				3.2 - 6.3			
AD41BS	3.2 (1/8")	4.8	100 U	6.3	1.0	0.8 - 1.5	3.2	147 / 95	PWL30 PRG510 PRG540 SRC55V
AD42BS		6.4				1.6 - 3.1			
AD43BS		8.0				3.2 - 4.7			
AD44BS		9.5				4.7 - 6.3			
AD45BS		11.1				6.4 - 7.9			
AD46BS		12.7				7.9 - 9.5			
AD48BS		15.9				9.5 - 12.5			
AD410BS		19.1				12.7 - 15.8			
AD52BS	4.0 (5/32")	7.0	100 U	7.9	1.3	1.6 - 3.1	4.1	222 / 154	PWL30 PRG510 PRG540 SRC55V
AD53BS		8.5				3.2 - 4.7			
AD54BS		10.2				4.7 - 6.3			
AD56BS		13.3				6.3 - 9.5			
AD58BS		16.5				9.5 - 12.5			
AD62BS	4.8 (3/16")	7.6	100 U	9.5	1.6	1.6 - 3.1	4.9	326 / 202	HR710 HR730 PRG540 SRC55V SR3
AD64BS		10.8				3.2 - 6.3			
AD66BS		14.0				6.3 - 9.5			
AD68BS		17.1				9.5 - 12.7			
AD610BS		20.3				12.7 - 15.8			
AD612BS		23.5				15.9 - 19.0			
AD616BS		29.8				22.2 - 25.4			

