



### REMACHE POP ABIERTO ACERO ZINCADO - ACERO

Código	Diámetro "D" mm (pulg)	Largo "L" mm	Envase	Diámetro "D1" mm	Rango de Agarre, mm	Diámetro Broca, mm	Resistencia, kg Tracción/Cizalle	Remachadora apropiada
<b>Zincado Brillante</b>								
SD42BS	3.2 (1/8")	6.4	100 U	6.3	1.6 - 3.2	3.3	193 / 134	PWL30 HR720 HR710 PRG510 PRG540
SD43BS		8.0			3.2 - 4.8			
SD44BS		9.5			4.8 - 6.4			
SD45BS		11.1			6.4 - 7.9			
SD46BS		12.7			7.9 - 9.5			
SD48BS		15.9			9.5 - 12.0			
SD52BS	4.0 (5/32")	7.0	100 U	7.9	0.5 - 3.2	4.1	259 / 186	PWL30 HR720 HR710 PRG540 PRG5200
SD53BS		8.5			1.5 - 4.8			
SD54BS		10.2			3.0 - 6.4			
SD56BS		13.3			5.0 - 7.9			
SD62BS	4.8 (3/16")	7.6	100 U	9.5	2.4 - 3.2	4.9	370 / 268	PWL30 HR720 HR710 PRG540 PRG5200
SD64BS		10.8			4.8 - 6.4			
SD66BS		14.0			7.9 - 9.5			
SD68BS		17.1			9.5 - 11.1			
SD610BS		20.3			12.7 - 13.5			

